

IN THE CLAIMS:

Please amend the claims as follows:

11.(currently amended): A flexible cable comprising:

a coaxial part comprising:

a flexible base; and

a first conductor pattern forming an inner conductor and a second conductor pattern forming an outer conductor, the flexible base being disposed between the first conductor pattern and the second conductor pattern so as to form an electrical insulation there between; and

~~a non-coaxial part~~ having a third conductor pattern for transmitting a signal disposed atop the flexible base, said third conductor pattern in addition to and apart from the first and second conductor patterns and outside of a coaxial type arrangement.

12. (currently amended): A flexible cable comprising:

a coaxial part comprising:

a first conductor pattern;

two band-shaped second conductor patterns disposed parallel to and respectively above and below said first conductor pattern, said two band-shaped second conductor patterns being wider than said first conductor pattern; and

an insulator interposed between said first conductor pattern and said two band-shaped second conductor patterns, said two band-shaped conductor patterns having through-holes through which said two band-shaped conductor patterns are electrically connected; and

a ~~non-coaxial~~ part set aside from said coaxial part and outside of a coaxial type arrangement, comprising:

a third conductor pattern for transmitting a signal.

13. (currently amended): A flexible cable comprising:

a coaxial part comprising:

a first conductor pattern;

a band-shaped second conductor pattern covering a top portion of said first conductor pattern;

a band-shaped third conductor pattern covering a lower portion of said first conductor pattern; and

an insulator interposed between said first conductor pattern and said band-shaped second and third conductor patterns,

said band-shaped second and third conductor patterns having through-holes through which said band-shaped second and third conductor patterns are electrically connected,

said through-holes being arranged at intervals so as to prevent an electromagnetic wave leak from sides of said first conductor pattern; and

a ~~non-coaxial~~ part set aside from said coaxial part and outside of a coaxial type arrangement, comprising.

a conductor pattern for transmitting a signal.

14. (currently amended): A flexible cable comprising:

a coaxial part including a first conductor pattern, two band-shaped second conductor patterns disposed parallel to and respectively above and below said first conductor pattern, said two band-shaped second conductor patterns being wider than said first conductor pattern, and an insulator interposed between said first conductor pattern and said two band-shaped second conductor patterns, said two band-shaped conductor patterns having through-holes through which said two band-shaped conductor patterns are electrically connected; and

a ~~non-coaxial~~ part disposed ~~on one side of~~ apart from said coaxial part and having a plurality of conductor patterns for transmitting signals and outside of a coaxial type arrangement.

15. (currently amended): A flexible cable comprising:

a base having a surface provided with a first terminal and a second terminal;

a first conductor pattern disposed on the surface of the base via a spacer and electrically connected to the first terminal;

a second conductor pattern for transmitting a signal, having a ~~non-coaxial~~ structure outside of a coaxial type arrangement, and electrically connected to the second terminal; and

a third conductor pattern disposed on an outer side of the first conductor pattern and forming a coaxial structure together with the first conductor pattern.

16. (previously added): The flexible cable as claimed in claim 15, wherein the second conductor pattern and the second terminal are connected via a through-hole.